



SECTION A-A

Tricab Product Code	Conductor	Barrel	Length	d1	d2	d3	Insulation Colour
	mm ²	mm	mm	mm	mm	mm	
A03-AMXX/8B.5WH	2 x 0.5 mm ²	8.0	15.0	1.5	2.8	4.9	White
A03-AMXX/10B.5WH		10.0	17.0				
A03-AMXX/12B.5WH		12.0	19.0				
A03-AMXX/8B.75LB	2 x 0.75 mm ²	8.0	15.0	1.8	2.9	5.2	Light Blue
A03-AMXX/10B.75LB		10.0	17.0				
A03-AMXX/12B.75LB		12.0	19.0				
A03-AMXX/8B1RE	2 x 1.0 mm ²	8.0	16.0	2	3.5	5.7	Red
A03-AMXX/10B1RE		10.0	18.0				
A03-AMXX/12B1RE		12.0	20.0				
A03-AMXX/8B1.5BK	2 x 1.5 mm ²	8.0	15.5	2.3	3.9	6.5	Black
A03-AMXX/10B1.5BK		10.0	17.5				
A03-AMXX/12B1.5BK		12.0	19.5				
A03-AMXX/18B1.5BK		18.0	25.5				
A03-AMXX/10B2.5GY	2 x 2.5 mm ²	10.0	19.5	2.9	4.6	8	Grey
A03-AMXX/12B2.5GY		12.0	20.0				
A03-AMXX/18B2.5GY		18.0	26.0				
A03-AMXX/10B4OR	2 x 4 mm ²	10.0	21.0	3.8	4.9	8.8	Orange
A03-AMXX/12B4OR		12.0	23.0				
A03-AMXX/18B4OR		18.0	29.0				
A03-AKXX/14B6GR	2 x 6 mm ²	14.0	26.0	4.9	6.3	9.3	Green
A03-AKXX/18B6GR		18.0	30.0				
A03-AKXX/14B10BR	2 x 10 mm ²	14.0	26.5	6.5	7.9	12.8	Brown
A03-AKXX/14B16IV	2 x 16 mm ²	14.0	32.0	8.3	11.6	19.3	Ivory

SPECIFICATION	
Material	Insulation: Polypropylene
	Barrel: High Conductivity Annealed Copper
Finish	Electrolytic Tin-Plated
Dimensions	As listed in the Table
Colours	As listed in the Table
Voltage Rating (V)	600
Operating Temperature (°C)	Pre-Insulate: -10 to +75
	Tin Plated: -40 to +130

Product Name	A03 BOOTLACE/FERRULE INSULATED, TWIN		
Document Title	PRODUCT SPECIFICATION	Document No	TCMS-ACC-015
Drawn by:	<i>D.F.</i> D.F.	*There is ±5% tolerance to the dimensional values due to manufacturing process variations. Drawings are not to scale and all dimensions are in millimeters. TriCab is not liable for any errors, omissions, etc, and reserves the right to modify the specifications at any time.	
			