



## Current distributor plug & socket 4p Screw D6-13.5 IP68

THH.624.A4A.L.R



### GENERAL INFORMATION

<b>Type of installation</b>	Plug and Socket connector
<b>Product configuration</b>	Plug and socket junction box <i>*Plug &amp; Socket connectors included in the kit</i>
<b>Locking mechanism</b>	Screw lock
<b>Colour</b>	Black (Plastic components) - Techno green (Rubber components)
<b>Overall dimensions (mm)</b>	65.0 x 61.0 x 25.0

## ELECTRIC DATA

No. connected cables	4
Circuit wiring diagram	Power/Signal
Current rating (AC/DC)	17.5A
Voltage rating (AC/DC)	500V AC
Impulse withstand voltage	4kV
No. poles	4
Marking	1-2-3-4
Terminations	Screw
Terminations Thread/Tightening torque	M3 - max. 0.8 Nm

## CONNECTION DATA

Multi-stranded conductor cross-section without ferrule MIN (mm <sup>2</sup> )	0.50
Multi-stranded conductor cross-section without ferrule MAX (mm <sup>2</sup> )	1.50
Solid conductor cross-section MIN (mm <sup>2</sup> )	0.50
Solid conductor cross-section MAX (mm <sup>2</sup> )	1.50
Cable sheath stripping length (mm)	6.00
Reccomended types of cable	H05xxx/H07xxx
Cable diameter MIN (mm)	6.00
Cable diameter MAX (mm)	13.50
Tightening torque of nut-cable gland	2.5 Nm

## ENVIRONMENT CONDITIONS

IP rating	IP68
Salt Mist	Salt mist test : EN60068-2-11:2000
Mating cycles	1000 cycles
Ambient temperature MIN/MAX (According to EN61984/EN60998)	-40°C/+125°C
Operating temperature MAX	+60°C
Proof Tracking Index (PTI)	PTI 175

## MATERIALS

Exterior body	PA66 GF UL94 V0
Connector	PA66 GF UL94 V0
Cable gland	PA66 UL94 V2
O Rings	TPE
Impulse withstand category	II
Pollution degree	2
Material property	Halogen Free
Contacts	Brass
Contact screws	Steel

## PRODUCT COMPLIANCES

IEC Approvals	EN 61984:2009
---------------	---------------

## COMMERCIAL DATA

EAN	8057457091220
Packing method	Individually packed ( KIT )
Type of packaging	Blister
Kit contents	 <a href="#">THH.624.A4A.LR.pdf</a>
Pieces/kit (pcs)	1
Pieces/box (pcs)	10
Weight per Piece (gr)	217.80
Overall dimensions of box (mm)	300 x 200 x 160
Corresponding code in Box	THH.624.A4A
Custom tariff number	85369010
Country of origin	ITALY

## APPROVALS

Please login to access this data.

## INSTALLATIONS SHEET

### Assembly instructions

File	Type	Size
 <a href="#">606002035_TH624_web.pdf</a>	PDF	1.84 MB

## DRAWINGS

### Drawings

File	Type	Size
 <a href="#">THH_624_A4A.pdf</a>	PDF	576.17 KB

## CAD FILES

Please login to access this data.

---

## MARKETING DOCUMENTS

Please login to access this data.

---