

J93 – TECHNO Plug Rapid-Connector



Advantages

- Quick, Robust and Safe
- **Toolless. Screw-less version.**
- Powerful and Compact
- IP68 Water and Dust Proof
- Maximum Resistance to tensile stresses with an excellent cable strain relief
- UV Radiation Resistant
- Halogen Free material

Material

- Body: PA66
- Contacts: Brass – Nickel Plated

Operating Temperature

- -40°C to +125
- -49°C to +257

Standards

- EN 60529
- EN 60998
- IEC 61984

Inspection and Testing

- Visual Inspection
- Physical Measurement
- IP68 Test by EN 60529
- Electrical Type test to IEC 61984

Description

TECHNO Plug Connectors allow electrical equipment installation to a high protection class, watertight in depths up to 30m.

A patented spring system connects the connector without the use of screws and tools.

The IP68 connection is made quickly and safely, when mated, without the use of cast resin, gel, or heat shrink tube.

The rapid connectors constitute a reliable interconnection system that guarantees flexibility and speed and reduces installation costs.

Specification

Product Code	Conductor Range	No. of Poles	Current Rating	Voltage Rating
	<i>mm²</i>		<i>A</i>	<i>V</i>
J93-AAXX/4P17	0.5 – 1.5	4	17.5	500
J93-AAXX/5P17	0.5 – 1.5	5	17.5	500

Notes:

- Tricab is not liable for any errors, omissions, etc., and reserves the right to modify the specifications at any time.
- All information above is intended for use only as a guide.