

## J94 – TECHNO Socket Rapid-Connector



### Description

TECHNO Socket Connectors allow electrical equipment installation to a high protection class, watertight in depths up to 30m.

**A patented spring system connects the connector without the use of screws and tools.**

The IP68 connection is made quickly and safely, when mated, without the use of cast resin, gel, or heat shrink tube.

The rapid connectors constitute a reliable interconnection system that guarantees flexibility and speed and reduces installation costs.

### Advantages

- Quick, Robust and Safe
- **Toolless. Screw-less version.**
- Powerful and Compact
- IP68 Water and Dust Proof
- Maximum Resistance to tensile stresses with an excellent cable strain relief
- UV Radiation Resistant
- Halogen Free material

### Material

- Body: PA66
- Contacts: Brass – Nickel Plated

### Operating Temperature

- -40°C to +125
- -49°C to +257

### Standards

- EN 60529
- EN 60998
- IEC 61984

### Inspection and Testing

- Visual Inspection
- Physical Measurement
- IP68 Test by EN 60529
- Electrical Type test to IEC 61984

### Specification

Product Code	Conductor Range	No. of Poles	Current Rating	Voltage Rating
	<i>mm<sup>2</sup></i>		<i>A</i>	<i>V</i>
J94-AAXX/4P17	0.5 – 1.5	4	17.5	500
J94-AAXX/5P17	0.5 – 1.5	5	17.5	500

### Notes:

- Tricab is not liable for any errors, omissions, etc., and reserves the right to modify the specifications at any time.
- All information above is intended for use only as a guide.