Z33 – 60T Aluminium Crimping Dies



Advantages

- Packed in durable plastic storage box
- Clear markings of die A/F
- Stamps die size on lug

Material

• Heat-Treated Carbon Steel

Inspection and Testing

- Visual Inspection
- Physical Measurement
- Crimping, Mechanical Pulling, and Temperature Rise Test to AS/NZS4325-1 and IEC61238-1-1

Description

TriCab Crimping Dies are suitable for 60 Tonne compression crimping tools. The die kit contains 2 sets of dies that are only suitable for use with 400mm2 to 630mm2 ALI-FLEX Conductors.

ALUMINIUM CRIMPING DIE SELECTION				
Aluminium Conductor Size	5			
mm²	mm	mm		
400	39.0	50		
500-630	43.2	50		

Specification

Product Code	Min AL	Max AL
Flouuct code	mm ²	mm ²
Z33-ABXX/400J6300	400	630

Notes:

- Tricab is not liable for any errors, omissions, etc., and reserves the right to modify the specifications at any time.
- All information above is intended for use only as a guide.

Head Office 33 Prohasky St, Port Melbourne Vic 3207 Australia Postal PO Box 5068, Garden City Vic 3207 Australia Administration Ph +61 3 9676 6000 Fax +61 3 9676 6001 admin@tricab.com www.tricab.com